

LED Under Cabinet Light



FDUC-23-9W-LED

T5 LED Bar

22 5/8" 9W LED Under Light

Factory Direct Lighting
 100 Shields Court, Markham,
 ON Canada L3R 9T5
 Tel: 905-944-1210 • 1-855-533-0743 |
 Toll Fax: 1-855-533-3294
<http://www.factorydirectlighting.ca>

Features

Housing

Durable extruded aluminum frame with frosted smooth lens. Suitable for dry location applications only. On-body on/off switch is provided for individual control (except 9" models).

LED Driver

Fixture is provided with built-in silent non-flicker electronic LED driver, 120V, 60Hz.

Light Output

This accent light is available in 3000°K, 4000°K colour temperature.

Dimming

Fixture is dimmable with industry standard TRIAC, ELV and Incandescent dimmers.

LED Characteristics

Powered by LED integrated strip that maintains uniform intensity with 70% lumens at 50,000 hours average life; with a minimum CRI of 80.

Beam Spread

The fixture lens provides for 160° beam spread.

Linking

Complete with a joiner, these no shadow linking fixtures can be linked up to 10 units in a single run.


Mounting Kit

Hardware provided for mounting fixture to standard horizontal surfaces or vertical wall surface.

Operating Temperature

-10°C~40°C (14°F~104°F).

SPECIFICATION	
Approved Location	Damp
Beam Angle	160°
CCT	3000°K / 4000°K /
Certification	cETLus
Connection Type	3-Wire
CRI	80+
Dimming	Yes
Dimming Technology	TRIAC / ELV / Incandescent
Lumens	759 / 779
Lumens per watt	84 / 87
Max. Operating Temp.	40°C
Min. Start Temp.	-10°C
Lumen Maintenance	70% @ 50,000 hrs
Rated Life	50,000 hrs
Voltage	120V
Warranty	3 Years
Wattage	Up to 5



Ordering Guide

FDUC-23-9W-LED- K
 30K:3000K
 40K:4000K

Accessories
 FDUC-HB (Hardwire Box with Switch)
 FDUC-FC (6" Flex Connector)
 FDUC-PC (3 Wire Power Cord)