



DESCRIPTION

The FD Garage Lighter is a utility ceiling-mount fixture for general applications in parking garages, covered walkways, canopies, designed for easy installation and maintenance. It combines a durable die-cast aluminum housing, high quality shock proof polycarbonate lens with UV inhibitors with the efficacy of LED IP-54 rated.

SPECIFICATION FEATURES

Construction

Die-cast aluminum housing

Controls:

Powered by the High Efficient Antron Driver

Electrical:

Long Life LED System complete with Electrical driver to deliver the optimal performance. LED's available in 4000K with typical CRI: 80. Ambient temperatures -40C to 40C. Regular rated 200,000 hours at 85C. Electronic drivers available in 120M and 347 Volt.

Driver and Module Access:

Drivers and Modules can be accessed by removing the lens

Finish:

Polyester powder-coated bronze finish, rust and corrosion proof

Diffusion:

Silicone perimeter lens gasket and closed-cell neoprene housing gasket seals out moisture and contaminants. High quality shock proof polycarbonate lens with UV inhibitors

Mounting:

By pre-positioned recessed knock out on the housing

Compliance:

cETLus and DLC4.0

Warranty:

5 years



**LED
GARAGE LIGHTER**

ORDERING CODE, ENERGY AND PERFORMANCE DATA


Model No.	Delivered LM	Input Watts	Voltage	Color Temp.	Efficacy Lm/W	Certification	Status
FDGA-40LED4K	3859	40	120M	4K	96	cETLus/DLC	Stock
FDGA-40LED4K	3859	40	347V	4K	96	cETLus	Stock
FDGA-60LED4K	5700	60	120M	4K	95	cETLus/DLC	Stock
FDGA-60LED4K	5700	60	347V	4K	95	cETLus	Stock

Option: FDYM-2502 Occupancy Sensor

SHIPPING DATA

Model No.	Gross Weight per Carton
FDGA-40LED4K	3.2KG/7lbs

FDGA-40



FDGA-60

