

Microwave Motion Sensor (1-10V), 120-347V

MFG Part Number FDSL-MS


SKU#100884







Use for following products: FDS-32-LED-3K4K5K-120-347V-D3 SKU#100881 FDS-46-LED-3K4K5K-120-347V-D3 SKU#100880

Dimensions








Technical Data

Detection Pattern


Ceiling Mounted



Operating voltage	12VDC
Operating current	1A (Max)
Output	
Stand-by power	<0.5W
Detection area	50%100%
Hold time	5s/30s/1min/10min
Daylight threshold	2Lux/30Lux/50Lux/ Disable
Stand-by period	$0s/30s/20min/+\infty$
Stand-by dimming level	10%/20%/30%/50%
Microwave frequency	5.8GHz±75MHz
Microwave power	
Mounting height	Max.2.5-4m/8.2-13.12ft
Detection range	Max.10m/32.8ft
Operating temperature	-20°C~+60°C
IP rating	IP20

Settings





ambient brightness.

Application Function Demo – Dimmable control/Corridor function



With sufficient daylight, even when motion detected, light remains OFF.



With insufficient daylight, when motion detected, light ON.



After last detection, the light will be dimmed down to the stand-by dimming level(10%, 20%, 30% or 50%) after holdtime.



After the stand-by period, light OFF.