


Pre-Select 5 CCT 6" Slim LED Light Panel

FDLED-6-R15W-5CCT SKU#101133




Durable Aluminum Body 5/8" Easy Installation **Tension Spring Clips** Low-profile, edge-lit design

- Edge-lit technology, no glare or dark spots, instant-on
- · No existing recessed housing or junction box required
- Dimming: TRIAC 10% 100%
- IC rated for direct contact with insulation
- Suitable for WET LOCATION
- Rated for a long life over 50,000 hours




DIMENSIONS



INSTALLATION

Cut Hole Size Ø6-1/4"(158mm)



| | SPECIFICATIONS |
|-----------------------|-----------------------|
| Model | FDLED-6-R15W-5CCT |
| Energy Star Unique ID | 3627148 |
| Watts | 15W |
| Lumen Output (lm) | 1230lm |
| Size | 6in |
| Default Driver Input | AC120V,60HZ |
| Color Temperature(K) | 5CCT Selectable |
| CRI | CRI90+ |
| Dimming | Triac Dimming |
| Power Factor | >0.9 |
| Approved Location | Wet Location |
| Air Tight | Yes |
| Operating Temp. | (-4°F~104°F) -20~40°C |
| Beam Angle | 120° |

| | PACKAGE |
|---------------|---------------|
| Weight.(g) | 366g |
| Qty/CTN (pcs) | 18pcs/CTN |
| Box Dimension | 555*375*190mm |
| Gross Weight | 8.78kg/CTN |

Accessories



